



 Tadano Faun ATF 60-4
60-T

TADANO FAUN ATF 60-4 (60-T)

DIN - 75%

ZWENKEN MET STEPELS 360°

A \ B	10,4 m	17,8 m	25,3 m	32,7 m	36,5 m	40,2 m
2,5 m	60,0					
3,0 m	50,0					
3,5 m	44,8	30,0				
4,0 m	41,0	29,0				
4,5 m	37,0	27,5				
5,0 m	34,3	26,2	17,0			
6,0 m	29,8	22,6	17,0	13,0		
7,0 m	25,3	20,0	15,8	13,0		
8,0 m	16,9	20,0	14,5	13,0	9,0	7,0
9,0 m		18,4	13,3	12,0	8,8	7,0
10,0 m		15,5	13,0	11,0	8,5	7,0
11,0 m		13,2	12,6	10,1	8,3	7,0
12,0 m		12,6	12,1	9,2	8,1	7,0
14,0 m		9,9	9,8	7,8	7,6	6,5
16,0 m			7,8	6,7	6,5	6,1
18,0 m			6,8	5,8	5,6	5,3
20,0 m			5,8	4,8	4,9	4,6
22,0 m			4,9	4,0	4,1	4,1
24,0 m				3,6	3,3	3,6
26,0 m				3,2	2,7	3,0
28,0 m				2,9	2,2	2,5
30,0 m				2,7	1,8	2,0
32,0 m					1,5	1,7
34,0 m					1,1	1,4
36,0 m						1,1

C 16,0 m			
D \ B	5°	17°	30°
10,0 m			
11,0 m			
12,0 m	2,20		
14,0 m	2,20	1,80	
16,0 m	2,20	1,80	1,30
18,0 m	2,15	1,75	1,30
20,0 m	2,05	1,65	1,25
22,0 m	2,00	1,60	1,25
24,0 m	1,90	1,50	1,20
26,0 m	1,85	1,45	1,15
28,0 m	1,70	1,35	1,15
30,0 m	1,55	1,30	1,10
32,0 m	1,45	1,25	1,05
34,0 m	1,35	1,15	1,00
36,0 m	1,30	1,10	1,00
38,0 m	1,15	1,05	0,95
40,0 m	0,90	1,00	0,90
42,0 m	0,75	0,85	0,90
44,0 m	0,55	0,65	0,75
46,0 m		0,45	0,50

A: Mastlengte

B: Sprei in m

C: Jiblengte

D: Jibhoek

Stempelbreedte:



Let op! Bij de te hijsen last moet(en) het hijsblok en de hulpgereedschap(pen) meegeteld worden.